

Assessment of Irrigation Water Use through GROUNDWATER EXTRACTION IN THE SEMIARID NORTHEAST OF BRAZIL

Sophia Dobkowitz Project: Geoecology III Field work: Oct – Dez 2012 in Iguatu, CE, Brazil

Supervisors:

Prof. Dr. Axel Bronstert Prof. Dr. José Carlos de Araújo

Introduction


- Semiarid climate: Low precipitation and high evapotranspiration lead to water scarcity
- Ceará: Water for irrigated agriculture is supplied at 56 % by surface reservoirs and 44% by groundwater abstraction
- Objective: Quantify and analyze the alluvial groundwater extraction in the study area
- Pump and demand based calculation
- Water balance of groundwater withdrawal and recharge




Typical landuse: Banana and cattle




The observed river reach in the dry season



Location of the study area



Flow-chart of the water balance



Pump based (P) and demand based (D) calculation

Methods

- Investigation of 14.5 km²; 200 wells in the alluvium of the river Jaguaribe near Iguatu
- Interviews about qualitative and quantitative aspects of water use
 - crop, cultivated area, irrigation system
 - Pump capacity, pumping hours per day
- Measurement of depth to water table




Different well types

Total cultivated crops [ha] | Gilipside |

The cultivated crops in the study area


Results

- Most wells are shallow
- Mainly applied irrigation method is inundation
- Irrigated acreage covers 40 % of the study area
- Most important crops: Pasture as food for cattle, banana
- 97.6 % of the abstracted water is used for irrigation
- 99.4 % of the groundwater extraction occurs in the dry season
- Pump based calculation exceeds demand based, difference: 15.5 %
- Groundwater recharge from precipitation is much lower than infiltration to the alluvium from the river



The applied irrigation systems





Maize Beans

